


## SPECIFICATIONS

| Size                                | Metric       | British         |
|-------------------------------------|--------------|-----------------|
| Max. Working Height <b>A</b>        | 7.80m        | 25ft 7in        |
| Max. Platform Height <b>B</b>       | 5.80m        | 19ft            |
| Overall Length <b>C</b>             | 1.86m        | 6ft 1in         |
| Overall Width <b>D</b>              | 0.76m        | 2ft 6in         |
| Overall Height(Rails Up) <b>E</b>   | 2.15m        | 7ft 1in         |
| Overall Height(Rails Down) <b>F</b> | 1.83m        | 6ft             |
| Platform Size(Length×Width)         | 1.67m×0.74m  | 5ft 6in×2ft 5in |
| Platform Extension Size <b>G</b>    | 0.90m        | 2ft 11in        |
| Ground Clearance(Stowed/Raised)     | 0.09m/0.016m | 4in/1in         |
| Wheelbase <b>H</b>                  | 1.36m        | 4ft 6in         |
| Turning Radius(Inside/Outside)      | 0m/1.64m     | 0in/5ft 5in     |
| Tyres                               | Φ323×100mm   | Φ323×100mm      |

| Performance                     |             |             |
|---------------------------------|-------------|-------------|
| S.W.L                           | 230kg       | 507lb       |
| S.W.L On Extension              | 113kg       | 249lb       |
| Max. Occupants (Indoor/Outdoor) | 2/1         | 2/1         |
| Gradeability                    | 25%         | 25%         |
| Travel Speed(Stowed)            | 4.5km/h     | 2.80mph     |
| Travel Speed(Raised)            | 0.6km/h     | 0.37mph     |
| Max. Working Slope              | X-1.5°/Y-3° | X-1.5°/Y-3° |
| Up/Down Speed                   | 21/25sec    | 21/25sec    |

| Weight         |        |        |
|----------------|--------|--------|
| Overall Weight | 1630kg | 3593lb |

| Power             |               |               |
|-------------------|---------------|---------------|
| Hydraulic Tank    | 6.5L          | 1.7gal        |
| Lead-acid Battery | 24V/185Ah     | 24V/185Ah     |
| Lithium Battery   | 24V/180Ah     | 24V/180Ah     |
| Charger           | 24V/30A       | 24V/30A       |
| Driving Motor     | 2×15VAC/0.5kW | 2×15VAC/0.5kW |
| Lifting Motor     | 16VAC/3kW     | 16VAC/3kW     |



## FEATURES

### Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Non-Marking Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- Charging Indicator
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button



### ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688

E-Mail: [export@cndingli.com](mailto:export@cndingli.com)

<https://en.cndingli.com>

Due to continuous technology updates, technical parameters are subject to change without notice. This picture book is for reference only, the actual product shall prevail. The copyright is owned by zhejiang dingli, any content may not be copied for any purpose without written permission.

2025-03

