



DIESEL RT SCISSOR LIFT

SR1018D / SR1218D

(SR3369D / SR4069D)

HIGHLIGHTS

LGMG SR18D Series rough terrain scissor lifts are specifically built for tough construction sites with four-wheel drive and fantastic gradeability. High load capacities with compact design provide a great combination for the larger working area and greater maneuverability through rough terrain job sites.


- High capacity, large platform with compact design maximises productivity.
- Powerful diesel engine and four-wheel drive make the machine ideal for varying conditions.
- Oscillating axels with great gradeability provide better performance on rough terrain job sites.
- Optional hydraulic outriggers deliver better stability on uneven ground.
- Intelligent self-diagnostic system for quick troubleshooting.



LGMG SR18D Series

SPECIFICATIONS

MODELS	SR1018D (SR3369D)		SR1218D (SR4069D)	
Measurements	Metric	US	Metric	US
Working Height Max.	11.7m	38.4ft	13.9m	45.6ft
A Platform Height-Raised	9.7m	31.8ft	11.9m	39ft
B Platform Height-Stowed	1.41m	4.62ft	1.56m	5.12ft
C Platform Length	2.79m	9.15ft	2.79m	9.15ft
D Platform Width	1.6m	5.25ft	1.6m	5.25ft
E Overall Length(with ladder)	3.12m	10.2ft	3.12m	10.2ft
F Overall Width	1.79m	5.81ft	1.79m	5.81ft
G Overall Height-Rails Up	2.55m	8.36ft	2.7m	8.86ft
Overall Height-Rails Down	1.89m	6.2ft	2.04m	6.69ft
H Extension Deck	1.52m	4.99ft	1.52m	4.99ft
I Wheelbase	2.29m	75.1 in	2.29m	75.1 in
Ground Clearance-Center	0.23m	0.75ft	0.23m	0.75ft
PRODUCTIVITY				
Platform Occupants Max. (in/out)	4/2	4/2	3/2	3/2
Platform Capacity	454kg	998.8lbs	365kg	803lbs
Platform Capacity-Extension	140kg	308lbs	140kg	308lbs
Drive Height	Full Height			
Gradeability-Stowed	35%			
Turning Radius-Outside	4.75m	15.6ft	4.75m	15.6ft
Raise/Lower Speed	39/46s		61/55s	
Brakes	Four-wheel Brake			
Drive Mode	4×4			
Tires Type	Foam-filled			
Tires Size	663×283mm	26×12in	663×283mm	26×12in
POWER				
Power Source	Kubota D1105 18.5kw/24.8hp			
Fuel Tank Capacity	53L	14gal	53L	14gal
HYDRAULIC SYSTEM				
Hydraulic Oil Capacity	70L	18.5gal	70L	18.5gal
WEIGHT				
Machine Weight without Outriggers(CE/ANSI)	3980kg	8780lbs	5120kg	10290lbs
Machine Weight with Outriggers(Optional)	4400kg	9700lbs	5080kg	11200lbs



STANDARD FEATURES

- Proportional control
- Foldable guardrails
- Self-lock entry gate
- Descent alarm with flashing beacon
- Tilt alarm with lift cut-out
- Overload sensing system
- Emergency stop button
- On-board diagnostic system
- Oscillating axle
- Horn/Hour meter
- Four-wheel drive and break
- Full-height drive

OPTIONAL

- AC power to platform
- Auto-leveling outriggers
- Platform anti-collision device
- Solid tires
- Solid non-marking tires
- Foam-filled non-marking tires
- Hydraulic generator
- GPS

Machines in compliant with EN280 / ANSI 92.20 Standard.

Specifications subject to change without notice. Photos and diagrams in the page are for promotional purposes only.
2020 V1 Version

LINGONG GROUP JINAN HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China
Email: sales@lgmg.com.cn Tel: +86-0531-67879283

LGMG Europe B.V.

Address: Laanweg 16 3208LC Spijkenisse Rotterdam, The Netherlands

LGMG North America, Inc.

Address: 1445 Sheffler Dr, Chambersburg, PA. 17201, USA



RELIABILITY IN ACTION